

Series P000 SOLENOID VALVE

Model#
P02003811F1DH

2-Way, Pilot Diaphragm Solenoid Valve,
Normally Closed

Technical Specifications

| | | |
|--------------------|-------------------------------|---------------------|
| Pipe Size (Inch) | Orifice Size (Inch) | Flow Factor (CV) |
| 3/8" | 7/16" | 3 |
| Voltage | Power | Min. Pressure (PSI) |
| 12VDC | 19W | 1.5 |
| | | Max Pressure (DC) |
| | | 217 |
| Temperature Range | Medium Examples | Sealing Material |
| 5° + 302° F | Light Oils, Air, Water | FKM |

Valve Dimensions

| | |
|--------|--------|
| (F.F): | 3/8" |
| (DN): | 7/16" |
| (LF1): | 33/64" |
| (LF2): | 1/2" |
| (L1): | 1"1/4 |
| (L2): | 1" |
| (L): | 2"1/4 |
| (A): | 1"5/8 |
| (H1): | 2"5/8 |
| (H): | 3"1/8 |
| (CH): | 1"5/16 |

Electrical Connection

| | |
|--------------------------|---------------|
| Rating: | NEMA 4/ IP 65 |
| Strain Relief Connector: | Model 020 |

